



UPSCALE TOUCHSCREEN INDICATOR

FOR STRAIN GAUGE & SAW LOAD CELL SCALES

www.arlynscales.com

The Arlyn UpScale Touchscreen Indicator is a new state-of-the-art digital indicator available exclusively from Arlyn Scales. It is equipped with a 7 inch HD IPS Capacitive 5-point widescreen touchscreen display with a resolution of 1024x600 (WSVGA) pixels. The Arlyn UpScale is driven by a powerful Quad Core processor and comes with a spacious 8GB of storage. It is also equipped with 2GB of DDR3 RAM giving it more than enough power to multitask across simultaneous processes.

Like the MKE-5, the UpScale features a robust water resistant enclosure, a swivel mount and context-aware user interface presented on its color touchscreen. The user experience is natural, allowing for intuitive navigation and function execution without the use of a manual. It can be equipped with multiple options such as RS-232, USB, Ethernet TCP/IP, 4-20mA and many more. It has a full Tare function including QuickTare, Tare Definition storage and recall.

Unlike the MKE-5, due to the versatility of its Android-based operating system, it can perform advanced operations that the MKE-5 Indicator and even 3rd party indicators cannot perform. Equipped with the right options, the UpScale can also report directly to a Google Spreadsheet, send emails at target weights, communicate in Modbus, perform Flow Rate measurements, scan and print barcodes as well as easily integrate to the AxChange Cloud Monitoring System. Visit <https://www.arlynscales.com/scales/arlyn-upscale-touchscreen-indicator/> for more information.

Product Code	Description
UPSCALE-9	Gray, Molded Plastic
UPSCALE-9-SS	Stainless Steel, NEMA 4x



UPSCALE-9



UPSCALE-9-SS

FEATURES

Standard Load Cell Connectivity – Compatible with any 4- to 6-wire load cell scale platforms.

Color Touchscreen – 7” IPS HD Capacitive WSVGA Color Touchscreen Display.

Context Driven UX – Buttons/Menus are based on features and options equipped to reduce clutter and increase productivity.

Flexible Outputs – Available with Wi-Fi, RS-232, USB, Ethernet TCP/IP, Setpoints, Analog 4-20mA, 0-5V.

Enhanced Functions – AxChange Cloud, Google Sheets, Automatic Emails at Target Weights, Modbus, Barcode Features, etc.

Water Resistant – Molded enclosure with rubber gasket seals out moisture.

ADDITIONAL SPECIFICATIONS

Dimensions (w/ Swivel Mount)

Plastic – 6” x 12” x 2.2”

NEMA 4x – 7.2” x 12” x 1.61”

Weight Display Modes

Normal – 0.5” High Character Display, 6 Digits

Scoreboard – 1.25” High Character Display, 6 Digits

Enclosure Material – Molded Plastic, Beige

Optional Enclosure – Stainless Steel, NEMA 4x

Load Cell Connector – M12, Wire Terminal, Custom.

Excitation (+/-) – 3.3VDC, 0V

Calibration – Fully unlocked Calibration Process

Operating Temp Range – 14 °F - 104 °F

LCD – 7” IPS HD Capacitive WSVGA Color Touchscreen

Weigh Features – Automatic Calibration, 8 unit conversions (lb, kg, g, oz, etc.), net/gross, keyboard, digital tare memory database w/ recall and search functions (barcode driven if equipped).

Filter Options – Software Filter, Stability Control, Zero Tracking, Motion Detect,

Output Options – RS-232, USB, Wi-Fi, Ethernet TCP/IP, Data Logging, Setpoint Control, Analog 4-20mA, 0-5V

Other Functions – Google Sheets, Emails, Modbus, Barcode. Other Options – Rechargeable Battery Pack, Parts Counting.

Mount – Table Top, Swivel Mount w/ mounting holes.